

Scale: 1/4" = 1'0"

PAR-31MAA-J

SPECIFICATIONS:

- On/Off

User functions allow user to set

- Operation modes cool, heat, dry, fan



Charles Washington Hall

RENOVATIONS

Corner of George & Washington Streets Charles Town, W.Va.

For the City of Charles Town City of Ranson

Planning & Engineering (prime) Hall Planning & Engineering, Inc 316 Williams Street Tallahassee, FL 32303

Landscape Architecture Stromberg/Garrigan & Assoc.,Inc. 102 E. Main Street-The Penn Bldg Somerset, PA 15501

Historic Preservation & Architecture Landmarks SGA, LLC 102 E. Main Street-The Penn Bldg Somerset, PA 15501

Structural Engineer

R.L. Silman Associates 1053 31st Street NW Washington D.C. 20007

Mech/Elect Engineer

Comfort Design, Inc. 620 Pennsylvania Avenue Winchester, VA 22601

Architect



Issue/Revision Seal 1 REVISED VRF MARCH 4, 2015

Drawing Title

Basement Mechanical Plan

Date 9/26/14 Drawing Number

Scale 1/4"=1'0" Project Number 11105

M2.1



Set temperature Fan speed setting Airflow direction Almow direction Timer Operation: Weekly Timer: On/Off/Temperature setting up to 8 times per day of the week in 1-minute increments Simple Timer: On and Off time can be set once within 72-hour period in 1 hour increments

Simple Timer: On and Off time can be set once within 12 means in 1-hour increments
Auto-off Timer: Turns indoor unit Off based on countdown time up to 4-hours in 30-minute increments
Room Temperature: Displays room temperature sensed either at the indoor unit (default) or at the remote controller
Set Temperature Range Limit: From the Backlit MA Controller, the allowable set temperature range can be reduced for cool and heat modes

Controls group operation for up to 16 indoor units in a single group
Features selectable multi-lingual LCD (English, Spanish, and French)
Supports both Fahrenheit and Celsius

- Supplemental heat function enable/disable
 Function Lock Out: Prohibits all functions or all functions except On/Off from the backlit MA controller
- Addressing: No addressing required
- Wiring: connects using two-wire, stranded, non-polar control wire to indoor unit connection terminal
 Dimensions: 4-3/4 x 3/4 x 4-3/4" (120 x 19 x 120 mm)