GROVE USA, LLC.
PAINT SHOP ALTERATIONS & OUTDOOR PAINT BUILDING
CONTRACTS NO. 24044-A GENERAL CONSTRUCTION
JULY 23, 2024

ADDENDUM NO. 2

TO ALL PROSPECTIVE BIDDERS:


Please note the following changes, corrections, additions, and/or information in connection with the contract and be otherwise governed accordingly. Receipt of this addendum must be acknowledged in the space provided in the Bid Form.


This addendum is hereby made a part of the Contract Documents.

GENERAL INFORMATION


- 1. Drawing X1.1 and X1.2 are revised to reflect changes to show the limit of work associated with the project and site. The disturbed areas are to be restored with the designated 12" thick reinforced concrete pad. The two Alternate A-1 and A-2 for concrete pads have been revised and a revised Bid Form is attached.
- 2. Drawing S1.3 is revised to reflect changes to eliminate the 6' X 6' equipment pads along the building and provide a 12" reinforced concrete pad as noted for supporting all exterior equipment and tanks associated with the Outdoor Paint Building.
- 3. Project sequence of construction at the site for the Outdoor Paint Building is not to start until February of 2025. Contractor may submit invoice after award of project for deposit required for initiation of their subcontract for Outdoor Paint Building. Field work for the office and second floor storage in the existing paint shop building can start in February of 2024. Field work for the overhead doors and crane in the existing Paint Shop Building cannot start until the Outdoor Paint Building is operational.
- 4. The Outdoor Paint Building supplier shall provide equipment start up and testing services upon issuance of substantial completion from Project Engineer and 'Certificate to Occupy" from local code official. Start-up services shall be to ensure equipment is properly set up, tested, adjusted and documented that system is fully functioning in accordance with intended use and compliance with the requirements of the system warranty. The service shall include operation and maintenance training as needed to ensure equipment will be properly operated and maintained in a safe and efficient manner. Provide operation documentation and instructions.
- 5. In restoring existing grade and trenching that is not designated to be finished with the 12" reinforced concrete slab, the area shall be paved over compacted subgrade with 6" 2A stone subbase, 4" bituminous base course, 2 1/2" bituminous ID-2 binder course and 2" ID-2 wearing course per PennDOT specifications.

END OF ADDENDUM NO. 2





ALL DOCUMENTS PREPARED BY DAVID BLACK ASSOCIATES, INC ARE INSTRUMENTS OF SERVICE WITH RESPECT TO THIS PROJECT THEY ARE NOT INTENDED OR REPRESENTED TO BE SUITABLE FOR REUSE BY OWNERS, CONTRACTORS, OR OTHERS ON EXTENSIONS OF THIS PROJECT OR ON ANY OTHER PROJECT. ANY REUSE WITHOUT WRITTEN VERIFICATION OR ADAPTION BY DAVID BLACK ASSOCIATES, INC. WILL BE AT THE OWNERS SOLE RISK AND WITHOUT LIABILITY OR LEGAL EXPOSURE TO DAVID BLACK ASSOCIATES, INC. THE OWNER SHALL INDEMNIFY AND HOLD HARMLESS, DAVID BLACK ASSOCIATES, INC. FROM ALL CLAIMS, DAMAGES, LOSSES AND EXPENSES ARISING OUT OF OR



David Black Associates, Inc.

